

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A method comprising:
receiving a first signal defining a reference time domain;
receiving a second signal defining a transport time domain asynchronous to the reference time domain; and
generating an isochronous network packet including a first timestamp indicating a point in time measured with respect to the reference time domain and represented as a measure of the transport time domain;
determining an output signal based at least in part upon the first signal;
dynamically sampling the first signal and the second signal to determine a scale factor and an offset factor between the reference and transport time domains; and
modifying the output signal by at least one of the scale factor and the offset factor to represent the output signal in terms of the transport time domain.
2. (Canceled)
3. (Currently Amended) The method of claim 2 1, wherein receiving the first signal comprises receiving a house reference signal.
- 3 4. (Previously Presented) The method of claim 1, wherein receiving the second signal comprises receiving at least one isochronous network packet including a second timestamp indicating an isochronous network cycle-time.
- 4 5. (Original) The method of claim 4 wherein the isochronous network cycle time is determined by an IEEE 1394 cycle master device.
- 5 6. (Original) The method of claim 1, wherein generating the isochronous network packet includes associating the timestamp with at least one frame of generated video data to be transmitted across an isochronous network.
- 6 7. (Original) The method of claim 1, wherein generating the isochronous network packet includes associating the timestamp with at least one frame of received video data to be transmitted across an isochronous network.
- 7 8. (Currently Amended) An article of manufacture comprising a machine readable medium having a plurality of machine readable instructions stored thereon, wherein when executed by a processor, the instructions cause the processor to:
receive a first signal defining a reference time domain;

receive a second signal defining a transport time domain asynchronous to the reference time domain; and

generate an isochronous network packet including a first timestamp indicating a point in time measured with respect to the reference time domain and represented as a measure of the transport time domain;

determine an output signal based at least in part upon the first signal;

dynamically sample the first signal and the second signal to determine a scale factor and an offset factor between the reference and transport time domains; and

modify the output signal by at least one of the scale factor and the offset factor to represent the output signal in terms of the transport time domain.

9. (Canceled)

8 10. (Currently Amended) The article of manufacture of claim 9, wherein the machine readable instructions that cause the processor to receive the first signal further cause the processor to receive a house reference signal.

9 11. (Previously Presented) The article of manufacture of claim 8, wherein the machine readable instructions that cause the processor to receive the second signal further cause the processor to receive at least one isochronous network packet including a second timestamp indicating an isochronous network cycle-time.

10 12. (Original) The article of manufacture of claim 11, wherein the isochronous network cycle time is determined by an IEEE 1394 cycle master device.

11 13. (Original) The article of manufacture of claim 8, wherein the machine readable instructions that cause the processor to generate the isochronous network packet further cause the processor to associate the timestamp with at least one frame of generated video data to be transmitted across an isochronous network.

12 14. (Original) The article of manufacture of claim 8, wherein the machine readable instructions that cause the processor to generate the isochronous network packet further cause the processor to associate the timestamp with at least one frame of received video data to be transmitted across an isochronous network.

13 15. (Currently Amended) An apparatus comprising:
means for receiving a first signal defining a reference time domain;

means for receiving a second signal defining a transport time domain asynchronous to the reference time domain; and

means for generating an isochronous network packet including a timestamp indicating a point in time measured with respect to the reference time domain and represented as a measure of the transport time domain;

means for determining an output signal based at least in part upon the first signal;

means for dynamically sampling the first signal and the second signal to determine a scale factor and an offset factor between the reference and transport time domains; and

means for modifying the output signal by at least one of the scale factor and the offset factor to represent the output signal in terms of the transport time domain.

16. (Canceled)

17. (Currently Amended) The apparatus of claim 15, wherein the means for receiving the first signal comprises means for receiving a house reference signal.

18. (Original) The apparatus of claim 15, wherein means for receiving the second signal comprises means for receiving at least one isochronous network packet including a timestamp indicating an isochronous network cycle-time.

19. (Original) The apparatus of claim 15, wherein the means for generating the isochronous network packet includes means for associating the generated timestamp with at least one frame of generated video data to be transmitted across an isochronous network.

20. (Original) The apparatus of claim 15, wherein the means for generating the isochronous network packet includes means for associating the generated timestamp with at least one frame of received video data to be transmitted across an isochronous network.

21. (Currently Amended) A system comprising:
a communications port to receive a first signal defining a reference time domain; and
a network interface to receive a second signal defining a transport time domain asynchronous to the reference time domain, and to generate an isochronous network packet including a timestamp indicating a point in time measured with respect to the reference time domain and represented as a measure of the transport time domain; and
synchronization logic to:
determine an output signal based at least in part upon the first signal,
dynamically sample the first signal and the second signal to determine a scale factor
and an offset factor between the reference and transport time domains, and

modify the output signal by at least one of the scale factor and the offset factor to represent the output signal in terms of the transport time domain.

22. (Canceled) ¹⁶

23. (Original) The system of claim ~~21~~¹⁶, wherein the network interface comprises logic to receive at least one isochronous network packet including a timestamp indicating an isochronous network time.

24. (Currently Amended) The system of claim ~~22~~¹⁴ ~~21~~¹⁶, wherein the synchronization logic further comprises logic to associate the generated timestamp with at least one frame of generated video data to be transmitted across an isochronous network.

25. (Currently Amended) The system of claim ~~22~~¹⁶ ~~21~~¹⁸, wherein the synchronization logic further comprises logic to associate the generated timestamp with at least one frame of received video data to be transmitted across an isochronous network.